



Vaisala AP10

Access Point for Radio Frequency Loggers

Access Point for Radio Frequency Loggers				AP10	1	2	3	4	5	6	7
1	Region Radio Frequency	FCC + CSA SRRRC ETSI Giteki KCC NCC	915MHz 500MHz 868MHz 920MHz 921 MHz 922MHz	For North America For China For Europe For Japan For Korea For Taiwan	A C E J K T						
2	Power Supply	PoE Only Power Supply with EUR-adapter Power Supply with US-adapter Power Supply with UK-adapter Power Supply with AUS-adapter Power Supply with all adapters				1 2 3 4 5 6					
3	Cable	None Ethernet Cable 2m					N A				
4	Connectivity to Monitoring System	viewLinc On Premise viewLinc Cloud Americas Data Center Custom Cloud Account, Americas Datacenter Jade Smart Cloud Americas Data Center Jade Smart Cloud Europe Data Center Custom Jade Smart Cloud Account, Americas Datacenter Custom Jade Smart Cloud Account, Europe Datacenter				0 1 5 6 E F					
5	User Guide	None Multilingual Quick Guide					N A				
6	Reserved 1	For Future Purposes									
7	Reserved 2	For Future Purposes									

Additional information

TOTAL
QTY
TOTAL VALUE

Selections in bold are included in the prices of the basic versions.

Example of order code with typical settings:

AP10 A 1 N 0 N 0 N

Most of our configured products have Order Forms in Excel format. Internal version of Order Form is the one that Configurator in EBS is based on.
This version needs to be stored in Aton to have it easily available and synchronized with EBS Configurator.
Internal Order Form is stored in Aton as a general document, see existing examples.
Important to note is that code begins with DOC, Desc1 is either "Order Form" or "Order Form, Internal" and Desc2 has product item code.
Order Form document card is linked into product item's relationship. compared to item structure.
Relationship to product item is needed to have validity dates to track order form revision changes

Spare Parts:

245127SP Universal Power Supply (15VDC, 0.8A, 12W)